

Delta Technical Coatings, Inc.

Material Safety Data Sheet

| | | | | |
|---|---------------------|---|-----------|--------------|
| IDENTITY (As Used on Label and List) Sobo Premium Craft Glue | | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. | | |
| SECTION I | | | | |
| Manufacturer's Name Delta Technical Coatings, Inc. | | Emergency Telephone Number (800) 423-4135 | | |
| Address 2550 Pellissier Place | | Telephone Number for Information (562) 695-7969 | | |
| Whittier, California 90601-1505 | | Date Prepared Rev. 3/19/01 | | |
| | | Signature of Preparer (optional) | | |
| SECTION II | | | | |
| Hazardous Components (Specific Chemical Identity, Common Name(s)) | | | | |
| None | | OSHA PEL | ACGIH TLV | Other Limits |
| | | N/A | N/A | N/A |
| | | | | |
| | | | | |
| SECTION III | | | | |
| Physical and Chemical Characteristics | | | | |
| Boiling Point | >240F | Specific Gravity (H ₂ O = 1) | 1.1 | |
| Vapor Pressure (mm Hg.) | N/A | Melting Point | N/A | |
| Vapor Density (AIR = 1) | >1 | Evaporation Rate (Butyl Acetate = 1) | <1 | |
| Solubility in Water Dilutable | | | | |
| Appearance and Odor A heavy bodied white liquid with a mild acrylic odor. | | | | |
| SECTION IV | | | | |
| Flash Point (Method Used) | | | | |
| N/A | Flammable Limits | LEL | N/A | UEL |
| Extinguishing Media Dry chemical, CO ₂ , water fog | | | | |
| Special Fire Fighting Procedures N/A | | | | |
| Unusual Fire and Explosion Hazards Product will not burn but may spatter if temperature exceeds boiling point. Dry film may burn and give off oxides of Carbon/Nitrogen. | | | | |
| SECTION V | | | | |
| Stability | | | | |
| Unstable | Conditions to Avoid | | | |

| | | |
|--------|---|-----|
| | | N/A |
| Stable | X | |

Incompatibility (Materials to Avoid)
Strong acids and alkalis.

Hazardous Decomposition or Byproducts
N/A

| | | | |
|--------------------------|----------------|---|---------------------|
| Hazardous Polymerization | May Occur | | Conditions to Avoid |
| | Will Not Occur | X | N/A |

| | | | |
|------------------|-------------|-------|------------|
| Routes of Entry: | Inhalation? | Skin? | Ingestion? |
| | No | No | No |

Health Hazards (Acute and Chronic)
None.

| | | | |
|------------------|------|-----------------|-----------------|
| Carcinogenicity: | NTP? | IARC Monographs | OSHA Regulated? |
| | No | No | No |

Signs and Symptoms of Exposure
Inhalation: No known signs or symptoms associated with exposure to product.

Skin & Eye: No known signs or symptoms associated with exposure to product.

Ingestion: No known signs or symptoms associated with exposure to product.

Medical Conditions Generally Aggravated by Exposure
N/A

Emergency and First Aid Procedures
Inhalation: Move subject to fresh air. Eye contact: Flush eyes with a large amount of water for at least 15 minutes.

Skin Contact: Wash affected areas thoroughly with soap and water.

Ingestion: If swallowed, give two glasses of water to drink. Consult a physician.

SECTION VI - Spill/Leak or Release Handling

Steps To Be Taken In Case Material Is Released or Spilled

Control spill with paper towel. Dried refuse may be disposed of according to local, state and federal regulations.

Waste Disposal Method

Dried refuse may be disposed of according to local, state and federal regulations. Check with local authorities for details on disposal.

Precautions to Be Taken In Handling and Storing

Avoid storing in areas exposed to direct sunlight. Keep from freezing temperatures. Store in a cool, dry place.

Other Precautions

Keep container tightly closed when not in use.

KEEP OUT OF REACH OF CHILDREN.

SECTION VII - Control Measures

Respiratory Protection (Specify Type)

| | | | | |
|-------------|----------------------|--------------|---------|------|
| Ventilation | Local Exhaust | Recommended | Special | None |
| | Mechanical (General) | May be used. | Other | None |

Protective Gloves

Impervious plastic or rubber.

Protective Glasses

Safety glasses may be worn to avoid eye contact.

Other Protective Clothing or Equipment

Long sleeve garments may be worn to avoid contact with skin.

Work Hygienic Practices

Clean-up with soap and water. Wash hands with soap and water after using product. Close container tightly.

SECTION VIII - Discharge

Delta Technical Coatings, Inc. Assumes no responsibility for personal injury or property damage to vendees,

users or third parties caused by the product. Such vendees assumes all risks associated with the use of this product.

HMIS SYMBOL

| | |
|-------------------|---|
| | 0 |
| | 0 |
| REACTIVITY | 0 |

RATING

| | |
|----------|---|
| SEVERE | 4 |
| SERIOUS | 3 |
| MODERATE | 2 |
| SLIGHT | 1 |
| MINIMAL | 0 |

Transportation Information:

D.O.T. : NR-Consumer Commodity
 I.A.T.A.: Not Regulated
 CERCLA RQ: None